

Construction	Multi Level Loop (Endless Design)	
Yarn	100% Universal (USA) Nylon 6	
Colour System	100% Solution Dyed	
Stitches & Gauge	Colorshift@8 Stitches per inch	
Total Tufted Pile Weight	33 Oz/Yd <sup>2</sup>	
Total Weight	6000 gm/m <sup>2</sup> (+/- 100 gm) (on PVC Back)	
Pile Height	5.0~8.0mm (+/-0.5mm)	
Primary Backing	Non Woven (UNITIKA-JAPAN)	
Secondary Backing	High Performance Precoat PVC Reinforced with Fiberglass	
Optional Backing	Anti-slip backing for glue free installation (lead time 60 days, MOQ 300 SQM/Colour)	
Tile Size	STOCKS IN SINGAPORE 60cm X 60cm	MADE TO ORDER- 50cm X 50cm or 100cm X 100cm (Lead time 60 days, MOQ 300 SQM/COLOUR)
Packing	14 TILES/BOX (5.04 SQM) (60cm X 60cm)	
<b>Test Standard</b>	<b>Test Report</b>	
Smoke Density Test	ASTM E 662 (Less than 450)	
Static Control	Lifetime Static Protection	
Fire Class	ASTM E 648-10 Class 1 (GB 8624-2012-B1) Flammability: 16 CFR 1631 Pass (For 100% Universal Nylon 6 Tested In Singapore)	
Formaldehyde Purification	Passes (JC/T 1074-2008) Class I	

